

model AT07

Tomasetto LPG pressure reducer, model AT07, is a two stages electronic reducer, suitable for traditional systems. Compact and reliable, it is homologated in accordance with the European Regulation ECE 67R-01. This reducer is developed from the previous model AT and equipped with a solenoid valve and an integrated filter unit to reduce the overall costs and permit an easier and faster installation. It is also provided with a double regulation system, to obtain always the best performance.

Four different versions, suitable for different engines, are available in our range. Upon request, a configuration with pressure compensation is available as well.

Maintenance kit: RGAT2060

Filter maintenance kit: RG



TECHNICAL DATA

Dimensions	150x160x110 mm
Weight	1,5 kg
Material	Die cast aluminium body, CNC machined
Max. inlet pressure	3 MPa
Solenoid voltage	12 V dc
Solenoid power	11 W
Inlet connection	Ø 6 mm M10x1
Outlet connection	Ø 20 mm

VERSION	LPG FLOW RATE	STANDARD	COMPENSATED
80 HP	16 kg/h	RGTA3530	RGTA3580
100 HP	22 kg/h	RGTA3500	RGTA3550
140 HP	30 kg/h	RGTA3510	RGTA3560
Super (>140 HP)	up to 40 kg/h	RGTA3520	RGTA3570